

Cylinder



www.DX-marine.com

DESIGN BY DX-MARINE

Capacity: 0.2L、0.3L、0.35L、0.45L

Safety pressure: 30MPa / 4500psi

Test pressure: 45MPa

Bursting pressure: >80MPa

Tear pressure: 85MPa

Thread specification: M18*1.5, each product has more than 9 teeth, ensuring absolute safety.

Material: 6061 high-precision aluminum (for aviation), high lightness and fatigue resistance.

The product uses 500t high pressure one time molding.

Wall thickness: ≥6MM, thick explosion-proof.

The high temperature thermal healing to prevent any welding.

Flat bottom standard H-type design is uniform, safe and reliable.

Applications: Grass aquarium aquaculture, medical emergency rescue, mountaineering, soda water machine CO2 supply, fire rescue and other occasions.

Parameter

Capacity (L)	Safety pressure (MPa)	Length * Diameter (cm)	Wall thickness (mm)	Weight (kg)
0.2	30	15*6.1	6.3	0.55
0.3	30	18.5*6.1	6.3	0.6
0.35	30	25*6.1	6.3	0.8
0.45	30	29.5*6.1	6.3	0.95



Jiangsu Dingxiang Marine Equipment Co.,LTD.

Professional fire fighting & life saving equipment manufacturer